



FEG-500A

**BLOCK FOR
ACCESSIBILITY**

FOCA[®]
SMART MOBILITY

BLOCK FOR ACCESSIBILITY

FEG-500A

TECHNICAL FEATURES

- Electronic turnstile in brushed stainless steel and frame of the top cover in carbon steel, coated with electrostatic powder paint, in black color;
- Cromed stainless steel arm;
- Closing of the arm in acrylic crystal with international symbol of accessibility;
- External edges of the electronic turnstile rounded;
- Modulate and customizable top cover to accommodate components, like displays, readers, keyboard, among others.
- Complete access and removal of the mechanical and electrical sets through the top cover;
- Internal components with treatment against oxidation;
- Electromechanical control of both directions (bidirectional)
- PI (Protection Index): 53;
- Supply voltage: 110/220 VAC, 50/60 Hz;
- Maximum power consumed: 30 W
- Maximum relative humidity for operation: 95% non-condensing
- Operation temperature: -10°C ~ 55°C.

OPERATION FEATURES

For operating modes in which the entry and/or exit access is controlled, the equipment will maintain the passage blocked until the control system (validator) sends a signal of release. The block can operate, receiving individual sign for each direction of the passage (entry or exit).

Once performed the passage, the arms' spin returns to be blocked, waiting for a new release signal. If the user does not start the passage within a period of a pre determined time (time-out), the access returns to be blocked.

For each performed access (entry or exit), the electronic interface of the block sends an individual signal for the end of the spin.

During the passage of the user, the mechanical system prevents the movement of the arms in the opposite direction of the authorized passage, besides guaranteeing the return to the locked position after the end of the access.

The control of the access is realized with only one locking solenoid for both directions, being energized only in unauthorized attempts crossings, avoiding unnecessary power consumption. In case of lack of electricity the passage will remain released for both directions.

Dimensions:

The exposed dimensions are from the standard Foca's model, possible alterations can be evaluated, according to the customer's needs.

- Foca reserves the right to make changes to its products without prior notice.

The Block for Accessibility FEG-500A was especially projected to attend and ensure the accessibility, in a safe and proper way, for users with reduced mobility. Developed with a focus on innovation, functionality and quality, it allows interface to various electronic systems of access.

APPLICATIONS: companies, schools, clubs, commercial buildings, bus terminals, among others.

OPTIONAL

- **Painted electronic turnstile:** electronic turnstile and top covers in carbon steel, coated with electrostatic powder paint, in the color black;
- **Stainless Steel electronic turnstile:** electronic turnstile and the top cover in brushed stainless steel;
- **Antipanic system (fall arms):** In a lack of electric energy or through an appropriate electrical pulse, the lock arm will automatically articulate to the vertical position, undoing the passage's barrier. To restore the standard operating state, the articulated arm must be manually returned to the lock position.
- **Operational pictograms:** Luminous indicated signal of authorization of the access (released or blocked)
- **Electromechanical counter:** component that registers the number of passages of entry and/or exit;
- **Collector box:** receptacle lodged in the interior of the electronic turnstile that collects the user's cards.
- **Mechanical control of access:** Unidirectional or bidirectional way of passage, without electrical interface of control.



FOCA has its own engineering and manufacturing departments and many customizations can be developed upon request.

